

Product Specification

CE-06



Name: CE-06

Car GPS tracker/vehicle GPS tracker

Feature list(vehicle gps tracker CE-06)

GSM Quad-band

GPS + GSM + GPRS wireless network

High sensitive GPS chipset

Real-time tracking

Built-in GSM & GPS antenna

Built-in ON / OFF power, wide voltage input range

Built-in acceleration sensor for vibration alarm

Support ACC detection, real-time reporting car status

Built-in 450mAh battery for alarm when the power supply is disconnected unexpectedly

Tele-cut off (petrol / electricity) function

SOS button for SOS alarm

Voice monitor function

Built-in CPU, eliminating breakdown automatically

Three LED indicators: GPS - Blue; GSM - Green; Power - Red

Check location via platform

Specifications (CE-06)	
Weight	96g
Dimensions	105.8 (L) × 54.5 (W) × 16.4 (H) mm
Working voltage / current	9-36vDC / 90mA
Operating temperature	-25°C - 60°C
Operating humidity	5% to 95% non-condensing
LED indicator	Three LED indicator: GPS-blue, GSM-green, Power-red
GSM	850 / 900 / 1800 / 1900 MHz
GPRS	Class12, TCP/ IP build in GSM Module
GPS	MT3326
GSM antenna	Built-in quad band
GPS antenna	Built-in GPS high gain ceramics patch antenna.
GPS Channels	20
Tracking sensitivity	-159dBm
Acquisition sensitivity	-144dBm
Locating time cost	Hot start: < 2 sec(open sky)
	Warm start: < 15 sec
	Cold start: < 38 sec(open sky)
LED indicator	Three LED indicator: GPS - Blue, GSM - Green, Power - Red
Battery	3.7vDC / 450mAh
Monitoring range	5M
Certifications	E - Mark, CE