

Product Specification

GPS Tracker CE-06



Technical Parameter:

Type: Vehicle GPS tracker CE-06

- GSM: 850/900/1800/1900 MHZ
- GPRS: Class12, TCP/IP build in GSM module
- GPS: MT3326
- GSM antenna: built-in quad band
- GPS antenna: built-in GPS high gain ceramics patch antenna
- GPS channels: 20
- Tracking sensitivity: -159dBm
- Acquisition sensitivity: -144dBm
- Locating time cost: Hot start: <2 seconds (Open sky)
Warm start: <15 seconds
Cold start: <38 seconds (Open sky)
- Application environment: Operating temperature: -25°C to +60°C
- Operating humidity: 5% to 95% non-condensing
- Battery: 3.7V DC / 450mAH
- Monitoring range: 5M
- Working voltage/current: 9-36V(another 9-80V),90mA.
- LED indicator: Three led indicator: GPS-blue, GSM-green, Power-red.

-Dimensions:98L*52W*15H mm.

-Weight: 80G.

Main features:

Type: GPS tracker CE-06

- 1.GSM Quad-band
- 2.GPS+GSM+SPRS wireless network
- 3.High sensitive GPS chipset
- 4.Real-time tracking
- 5.Built-in GSM&GPS antenna
- 6.Built-in ON/OFF power,wide voltage input range
- 7.Built-in acceleration sensor for vibration alarm
- 8.Support ACC detection, real-time reporting car status
- 9.Built-in 450 mAh battery for alarm when the power supply is disconnected unexpectedly
- 10.Tele-cut off(petrol/electricity) function
- 11.Check location information via SMS and GPRS(TCP)
- 12.SOS button for SOS alarm
- 13.Voice monitor function
- 14.Built-in CPU, eliminating breakdown automatically
- 15.Three LED indicators: GPS-blue, GSM-green. Power-red
- 16.Check location via platform.